Used at construction sites and plants!!

Container Rotating High-viscosity Mixer





Revolution in container holders!! Just pick up and

place material drum for easy setup!! Easy to set up on carrying area approximately 30cm from the floor!!

```
Easy to
transport!!
Large casters
ensure stable
transport!
Enables easy
transport over
uneven surfaces.
```

2

POIN1

Possible to mix at different angles!!

Easy to adjust angle by loosening screws!!

Dimensions / Part Names(Unit: mm)

- ⑤ Butterfly bolt for fixing mixing vane 6 Support pole for mixing vane ⑦ Power switch
- (8) Mainspring, 15 minutes timer (With operation lamp)
- (9) Mixing vane for normal rotation

350



① Tires for transport

2 DERARAKU holder

③ Handle for mixing

and transport

④ Mixing motor

angle adjustment



- Simple holder for container placement
- Adopted DERARAKU holder for easy carrying and placement of material drum!! Structure that holds the handle to enable straight or taper drums.
- Body with low center of gravity
- Realized stability with low center of gravity! Safe to use in a construction site with bad footing •Features handle for transport and large casters
- Large casters ensure stable transport!
- Easy to carry over uneven surfaces. Able to load onto commercial vehicles!! Possible to mix at an angle
- Possible to mix with the unit at an angle by stretching up transport handle.

Standard Specifications

Attachable container	20L pail (straight/taper)
Mixing vane	With one iron vane (Select from straight
Power supply / Electric capacity	100V · 10A
Mixing motor	400W
Container rotation speed	Fixed speed (50Hz:50rpm / 60Hz:60rpm)
direction	Automatic reversed rotation
Timer	Mainspring, 15 minutes (continuous oper
Weight	43kg

*Specifications and outside appearance may change without advanced notice. *The device is not explosion- or water-proof.

*Special specifications other than those noted above are available (optional). Please inquire with our sales representative if you wish to add optional specifications

⊕Use

•Mixing resin mortar •Mixing of urethane, epoxy and silicone •Preparation for high-viscosity grease

HARD MIXER SERIES [DERAMAZE]







t can / taper can)	
n)	
eration possible)	

Option



Mixing vane for normal rotation With Teflon® packing





Universal holder Corresponds to container sizes \$\phi 220 to \$\phi 300\$