Enables mixing and degassing of large volume at the best speed!!

Contaiber Rotating Vacuum Degassing Mixer







The operation panel is located at hand to improve workability. Easy-to-operate digital panel specifications

It is easy and convenient to operate. Timer set to be adopted digital panel! It reduces setting mistakes and makes work easier and more secure.



Uses a Dela-Raku holder!

Easy set by simply lifting and placing the material can!
The lifting height is also low, making it easy to attach and detach the container.



Vacuum pump placed outside

Easy oil change and management!

Maintenance has also become easier.

Use Use

- Mixing screen ink
- •Degassing and mixing adhesives for electronic parts
- Degassing and mixing silicone rubber

■ Dimensions / Part Names (Unit: mm)

- ① Vacuum-exhaust valve
- ② Vacuum gauge
- 3 Speed shift knob
- 4 Digital mixing timer Mixing start switch
- ⑤ Power switch
- 6 Power lamp

- 7 Power lamp built-in vacuum pump switch
- Acrylic sight window
- Vacuum chamber
- 10 Caster with stopper
- 11) Level bolt





■Standard Specifications

Attachable container	20L pail(straight/taper)
Mixing vane	With 20L dedicated mountain-shaped iron vane (With Teflon)
Power supply/Electric capacity	100V • 15A
Mixing motor	400W
Container rotation speed/direction	Variable speed (∼60rpm) • Automatic reversed rotation
Timer	Digital • 1~99minutes
Weight	150.5kg (Main unit 135.5kg+Vacuum chamber 15kg)
Vacuum pump	50Hz:141.7L/Min•60Hz:166.7L/Min
Vacuum gauge	Bourdon tube type -0.1MPa

**Model specifications, appearance, etc. are subject to change without notice **It is not explosion-proof and waterproof.

**All specifications other than the above are special specifications (options), so please contact our sales staff if you have any requests.

■Standard vane

